



“Get the power everywhere with you”

Product Catalog

DAS B-44



GENERATING RATES		PRIME	STAND BY
Power	KVA	40	44
Power	KW	32	35
Current	A	58	63
Standard Voltage	V	400/230	
Revolution Per Minute	r.p.m.	1500	
Rated at power factor	Q	0,8	

STAND BY POWER;

Supplying of emergency electrical power at variable load, in the event of normal utility power failure. This rating is maximum power, no overload capability is available.

PRIME POWER;

Supplying of electrical power at variable load for an unlimited number of hours in the event of normal utility power failure. 10% over load capability is available.


STANDARD FEATURES

- 4 Stroke, 1500 RPM, water cooled heavy duty diesel engine
- Protection system on manual run
- Flexible oil pipes and oil draining valve
- Pre-heater
- Lubrication oil and anti-freeze
- 4 Poles, synchron type, single bearing, brushless alternator
- Batteries and cables
- Electrostatic paint coated, steel, welded chassis
- Fuel tank housed in the chassis.
- Industrial type silencer
- Electronic battery charger
- Electrical wiring diagram
- User manual and operating manual

OPTIONAL EQUIPMENTS

- Sound proof canopy
- Automatic transfer switch
- Circuit breaker
- Trailer
- External fuel tank
- Heating system for fuel tank
- Oil heater
- Fuel filling system (Automatic / Manual)
- Analog indicators
- 1 Phase - 3 Phase switch plugs
- Alarm system for fuel level
- Remote control and monitoring

ENGINE SPECIFICATIONS

Brand		BAUDOIN
Model		4M06G50/5
Engine Power Stand BY	(kWm / hp)	44/48
Revolution Per Minute	(r.p.m.)	1500
Total Displacement	(L)	2.3
Cylinders Orientation		4 SINGLE
Bore x Stroke	(mm x mm)	89 x 82
Compression Orientation		17,5;:1
Governor Type		MECHANIC
Aspiration System		NATURAL
Injection		DIRECT
Cooling		WATER COOLED
Electrical System	(VDC)	12
Lub-Oil Capacity	(L)	11,5
Engine Coolant Capacity	(L)	12,9
Fuel Tank Capacity	(L)	70
Maximum Exhaust Temperature	(°C)	
Maximum Exhaust Gas Flow	(m3/h)	
Maximum Allowed Back Pressure	(kPa)	
Cooling Air Flow	(m3/min)	
Fuel Consumption 50 %	(L/h)	5,4
Fuel Consumption 75 %	(L/h)	7,8
Fuel Consumption 100 %	(L/h)	10,7

- Replaceable cylinder jacket • Dry type replaceable oil filter • Heat-resistant radiator for 50 °C


ALTERNATOR SPECIFICATIONS

Output Voltage	(V)	400/230
Frequency	(Hz)	50
Stationary Voltage Regulation	(±)	1 %
Short Circuit Current		> 300 %
Insulation		H
Protection		IP 23
Efficiency	(%)	88,1
Overloading		110 % FOR 1 HOUR
Power Factor	(Qi)	0.8
Total Harmonic Distortion Rate		THF < 2 %
Connection Type		STAR
Number Of Pole		4
Number Of Bearing		SINGLE

- 4 Poles, Self-Excitation and Self-Cooled, Brushless, Synchronotype alternator • Electronic type automatic voltage regulator (AVR)

DIMENSIONS WITHOUT CANOPY

- Diesel and gas genset support
- 400Hz operation support
- 400 event logs, full snapshot
- All parameters frontpanel editable
- 3 level configuration password
- 128x64 graphical LCD display
- Downloadable language
- Waveform display of V & I
- Harmonic analysis of V & I
- Synchro scope & checksynch
- Allows closed transfers
- 16Amp MCB & GCB outputs
- 8 configurable digital outputs
- Outputs expandable to 40
- 4 configurable analog inputs
- Both CANBUS-J1939 & MPU
- 3 configurable service alarms
- Multiple nominal conditions
- Multiple automatic exerciser
- Weekly operation schedule
- Dual mutual stand by with equal aging of gensets
- Manual "speed fine adjust" on selected ECUs
- Automatic fuel pump control
- Disable protections feature
- Excess power protection
- Reverse power protection
- Overload IDMT protection
- Load shedding, dummy load
- Multiple load management
- Current unbalance protection
- Voltage unbalance protection
- Fuel fulling & fuel theft alarms
- Battery back-up real time clock
- Idle speed control
- Battery charge run enabled
- Combat mode support
- Contactor & MCB drive
- 4 quadrant genset power counters
- Mains power counters
- Fuel fulling counter
- Fuel consumption counter
- Modem & Ethernet diagnostics
- Configurable through USB, RS-485, Ethernet and GPRS
- Free configuration program
- Allows SMS controls
- Ready for central monitoring Ethernet and GPRS
- Mobile genset support
- Automatic GSM geo-location
- GPS connectivity (USB & RS232)
- Dynamic DNS support
- Easy USB firmware upgrade
- IP65 rating with standard gasket

DIMENSIONS AND WEIGHT


Length (L)	mm	2270
Height (H)	mm	1500
Width (W)	mm	1000
Wet weight	kg	600
Fuel Tank Capacity	L	70

DIMENSIONS AND WEIGHT


Length (L)	mm	2270
Height (H)	mm	1750
Width (W)	mm	1000
Wet weight	kg	908
Fuel Tank Capacity	L	70



“Get the power everywhere with you”

İvedik OSB, the 1405 Avenue No: 1 Yenimahalle/Ankara

T: 0850 241 06 83

www.daspower.com.tr

info@daspower.com.tr

Contact Us

